



## AT126 & AT128

### Feature:

- Advanced Hot-Wire Alcohol Sensor
- Quick response
- SMD assembling, stable performance
- MCU control
- Cartoon and LCD indication, backup light
- Portable and small design
- No touch Healthy design
- Sensor fault self-checking
- Battery saved design, low voltage warning



AT126



AT128

Sensor	Hot-Wire Alcohol Sensor	Hot-Wire Alcohol Sensor
Range of measurement	0.00-1.00mg/L; 0.00-0.20%BAC 0.00-2.00g/L; 0.00-2.00%BAC	0.00-1.00mg/L; 0.00-0.20%BAC 0.00-2.00g/L; 0.00-2.00%BAC
Alarming Level	0.25mg/L;0.50g/L;0.05%BAC;0.5%BAC	0.25mg/L;0.50g/L;0.05%BAC;0.5%BAC
Accuracy	±10% F.S	±10% F.S
Battery pack	2 × AAA batteries	2 × AAA batteries
Working Environment	Temperature: -10℃~50℃ Relative Humidity: ≤93% No Dews	Temperature: -10℃~50℃ Relative Humidity: ≤93% No Dews
Warm-up time	<18 sec	<18 sec
Response Time	<8 sec	<8 sec
Display	3 digital LCD with cartoon indication	3 digitals LCD with cartoon indication
Dimension	103×37×19 mm	90mm ×30mm × 16mm
Weight	≤45g (excluding batteries)	≤45g(excluding batteries)
Certificate	CE & RoHS	CE & RoHS
Package	Colorful giftbox package, 100pcs/carton Carton size: 33*39*45cm Weight/carton: 9.00Kgs	Colorful giftbox package 100pcs/carton Carton size: 33*39*45cm, Weight/carton: 9.00Kgs.



Global Control C.A.

Gas Detection, Instrumentation & Industrial Safety  
 AV. Bolivar Norte C.C. Camoruco Piso 15 Ofic. 15-8 Valencia  
 Telfs: (0241) 8244157 - 8212318 Fax: (0241) 8234276  
 Cel : 0414-3405156  
 www.globalcontrol.com.ve e-mail: info@globalcontrol.com.ve  
 RIF: J-30531830-1 NIT: 0089648157