

GPT100 Portable Gas Leakage Detector

GPT100

For professional gas pipelines maintenance persons to check the leakage

Features:

- Advanced 16 bit MCU
- STN Dot Matrix LCD Display
- Adjustable Sensitivity and Zero Point
- Self-Test Function
- Low Battery Indicating
- Intrinsically Safe Design

Specifications:

Gas Detected: CH₄, C₃H₈, H₂
Range: 0-1000ppm (Times 10)
0-10000ppm(Times 100)
Indication:
LCD bar and digital indication of concentration
Different alarming tone for different concentration
Temperature Range: -20°C to 60°C
Humidity Range: 5 to 95% RH, non-condensing
Response time(T90): T<5s
Power: DC3.6V lithium battery, 2100mAh, rechargeable
Charge Time: 4-6 Hours
Operating Time: 12-70 Hours
Ingress Protection: IP54
Weight: 300g
Dimensions: 170×77×33mm



GPT100



Global Control C.A.

Gas Detection, Instrumentation & Industrial Safety

Av. Bolívar Norte C.C. Camoruco Piso 15- Ofic. 15-8 Valencia

Telfs: (0241) 8244157 - 8212318 Fax: (0241) 8234276

Cel : 0414-3405156

www.globalcontrol.com.ve e-mail: info@globalcontrol.com.ve

RIF: J-30531830-1 NIT: 0089648157

